

DATA SHEET

Item: PONGEE

Nº : 7031

Weight: 70 g/m²

Wide: 160 cm

Composition: 100% PE

Technical Properties

Description	Value	Norm
Seam slippage (mm) Warp/Weft	6	BS 3320 (6 Kg)
Seam slippage (mm) Weft/Warp.	10	BS 3320 (6 Kg)
Tear resistance (Elmendorf) (g) Warp.	3349	UNE EN ISO 13937-1
Tear resistance (Elmendorf) (g) Weft.	2397	UNE EN ISO 13937-1
Breaking strength (kg) Warp	75	UNE EN ISO 13934-1
Breaking strength (kg) Weft.	43	UNE EN ISO 13934-1
Grain line.	2(3)	standard test
Abrasion reistence (rev).	5	UNE EN ISO 12945-2 2000c

Dimensional Stability

Description	Value	Norm
Dimensional stability to steam ironing (%) Warp.	3,5	standard test (2 p)
Dimensional stability to steam ironing (%) Weft	1	standard test (2 p)
Dimensional stability to water cleaning (%) Warp	1	standard test (40°C)
Dimensional stability to water cleaning (%) Weft	1,5	standard test (40°C)

Colour Fastness

Description	Value	Norm
Colour fastness to wash.	4	ISO 105/C01 1978 (40°C)
Colour fastness to water.	4	ISO 105/E01 1978
Colour fastness to acid sweat.	4	ISO 105/E04 1978
Colour fastness to alkali sweat	4	ISO 105/E04 1978
Colour fastness to dryclean.	4	ISO 105/D01 1982
Colour fastness to dry rubbing	4	ISO 105/X12 1984

Textile Care Symbols

