

Sponsor:
On behalf of VPF-Amsterdam



T25372		8008.XX	
T25372	150	C0600	T599

59032090

SPEC SHEET

Composition

75% Viscose / 25% Polyamide + PU COATED

Fabric properties

Usable width	.	150,0 CM
Full width	Full width	154,0 CM
Weight with a deviation of 5%	EN 12127 meth 5	116 G/M ²

Mechanical properties

Shrinkage wash 40°C warp	ISO 5077 2007	7 %
Shrinkage wash 40°C weft	ISO 5077 2007	4 %
Tensile strength warp	ISO13934-1 2013	460 N
Tensile strength weft	ISO13934-1 2013	420 N
Tear resistance Elmendorf warp	ISO13937-1 2000	12 N
Tear resistance Elmendorf weft	ISO13937-1 2000	12 N
Seam slippage warp 80 N	ISO13936-2 2004	2,0 MM
Seam slippage weft 80 N	ISO13936-2 2004	3,0 MM
Spraytest	EN 24920	3
Watercolumn	EN20811/ISO811	1800 MM

Colourfastness

		Light	Middle	Dark	Change
Colourfastness to washing 40°C	ISO105C06 2010	4/5	4	3/4	
Colourfastness to dry cleaning	ISO105D01 2010	4/5	4	3/4	
Colourfastness to water	ISO105E01 2013	4/5	4	3/4	
Colourfastness to rubbing dry	ISO105X12 2001	5	4	4	
Colourfastness to rubbing wet	ISO105X12 2001	4/5	3/4	3/4	
Colourfastness to light	ISO105B02 2014	4/5	4/5	4/5	

Washing symbols



Remarks

Remark	-	PROVISIONAL DATA SHEET
--------	---	------------------------

VPF-Amsterdam +31 20 6116005 www.vpf-amsterdam.nl E-mail: info@vpf-amsterdam.nl



* The values on this sheet are solely indicative and are in no way binding