

# Kalahari 8414

## GENERAL INFORMATION

Composition	100% PES
Weight g/m <sup>2</sup>	280g
Weight g/Lm	406g
Width	145cm
Min. usable Width	138cm
Piece Length	50m
Tariff code	54076130

## CLEANING INSTRUCTIONS



## TECHNICAL DATE

• <b>MARTINDALE ABRASION</b> ISO12947-2 1998	<b>END POINT</b> <b>CHANGE IN COLOR</b>	>70000 4/5
• <b>SEAM SLIPPAGE</b> EN ISO 13936-2	<b>WARP</b> <b>WEFT</b>	2mm 2mm
• <b>TEAR STRENGTH</b> EN ISO 13937-3:2000	<b>WARP</b> <b>WEFT</b>	70N 46N
• <b>TENSILE STRENGTH ISO</b> 13934-1	<b>WARP</b> <b>WEFT</b>	1007N 1294N
• <b>COLOUR FASTNESS FOR RUBBING</b> EN ISO 105-X12	<b>WARP DRY</b> <b>WARP WET</b>	4 3/4
• <b>COLOUR FASTNESS TO LIGHT</b> EN ISO 105-B02	<b>GRADE</b>	122: 4 / 5
	<b>GRADE</b>	123: 4
	<b>GRADE</b>	124: 4
	<b>GRADE</b>	126: 3 / 4
	<b>GRADE</b>	127: 3
	<b>GRADE</b>	129: 4
	<b>GRADE</b>	210: 4
	<b>GRADE</b>	211: 3/4
	<b>GRADE</b>	212: 3/4
	<b>GRADE</b>	313: 4+
	<b>GRADE</b>	411: 3/4
	<b>GRADE</b>	511: 3/4
	<b>GRADE</b>	512: 4
	<b>GRADE</b>	518: 3/4
	<b>GRADE</b>	519: 4+
	<b>GRADE</b>	520: 4+
	<b>GRADE</b>	521: 4
	<b>GRADE</b>	522: 4
	<b>GRADE</b>	611: 4
	<b>GRADE</b>	613: > 4
	<b>GRADE</b>	616: 3/4
	<b>GRADE</b>	712: 4/5

# Kalahari 8414

<b>GRADE</b>	713:4/5
<b>GRADE</b>	717: 3 / 4
<b>GRADE</b>	810: 4
<b>GRADE</b>	811: 4+
<b>GRADE</b>	813: 4+
<b>GRADE</b>	814: 4+
<b>GRADE</b>	816: > 4
<b>GRADE</b>	817: 4+
<b>GRADE</b>	819: 4
<b>GRADE</b>	820: 3
<b>GRADE</b>	911: 5
<b>GRADE</b>	914: 4/5
<b>GRADE</b>	915: 4+
<b>GRADE</b>	918: 4+

- PILLING ON MARTINDALE**  
 ISO 12945-2:2000
 

<b>500 RUBS</b>		4/5
<b>1000 RUBS</b>		4/5
<b>2000</b>	<b>RUBS</b>	4/5
<b>5000 RUBS</b>		4/5
- COLOUR FASTNESS TO WATER**  
 ISO 105-E01
 

<b>STAINING TO WOOL</b>	4
<b>STAINING TO ACRYL</b>	4/5
<b>STAINING TO POLYESTER</b>	4
<b>STAINING TO NYLON</b>	3/4
<b>STAINING TO COTTON</b>	4
<b>STAINING TO ACETATE</b>	3/4
<b>CHANGE IN COLOUR</b>	4/5